



Alphanumeric pager AP-700

Equipped with 4 navigation buttons and the TFT display of white backlit. The Alkaline battery AAA is easy to replace. The display is compatible with 4 lines to 2 lines Zoom Display for larger view. Letters capacity is up to 28,672 (POCSAG). The long standby time up to 26 days is applicable to the hospital, , warehouse and logistics.. etc.

Product Description

- Up to 8 capcodes Capability for POCSAG
- 4 Keys Operation, User Friendly Interface
- 4 Lines, Total 84 Alphanumeric One Page Display
- Large Memory Size; Total Capacity 28,672 Letters for POCSAG
- 16 Memory Slots, 10 Sets Full Message
- 4 Beep Alerts, 10 Melody Alerts , Vibration Sleep Mode
- 5 Daily alarm Sets

Product Description

- 8 Message Locks
- 10 Personal Extra Personal Slots
- Synthesized or Crystal Type
- True Pocket Size
- White Back-light, Large Display Message Full Indicator
- Long Battery Life
- Mail Drop Alert
- Real Time Clock Calendar
- Extensive Compatibility
- Duplicate Message Indicator
- Unread Message Display
- Message Time Stamp
- Month, Date, Year, Time Display
- Selective Message Lock/Delete
- Lithium Battery Backup
- Reminder Alert / Zoom Feature
- PC or hand Programmable
- Support Languages: English, Spanish, Portuguese, Russian, German, and French

ACCESSORIES



Holder

Additional Information

Frequency	VHF 135~174MHz ; UHF 430~470Mhz
Paging Sensitivity	VHF 512bps-4 μ V/m, 1200bps-6 μ V/m, 2400 bps-8 μ V/m ; UHF 512bps-3 μ V/m, 1200bps-4 μ V/m, 2400 bps-5 μ V/m
Bit Rate	512/1200/2400bps for POCSAG
Channel Spacing	12.5KHz,25KHz
Code Format	POCSAG
Spurious Rejection	40dB below carrier
Alert Ton Loudness	87db @ 10 cm
Capcodes	8 Capcodes for POCSAG
Battery	AAA Alkaline batteries
Dimension	73(L)x50(W)x20(H)mm
Weight	49.5g